ISO 9001: 2015 CERTIFIED

Civil Aviation Authority of Fiji

Application for the inclusion of the BN2 Aeroplane Type in Aircraft Rating of a Pilot's Licence (Aeroplanes)

Form PL 105J

IMPORTANT

Before completing this form the notes of page 3 should be read carefully. Completed applications should be sent to the Civil Aviation Authority of Fiji, Private Mail Bag (NAP 0354), Nadi Airport, Fiji, together with the licence. Your attention is drawn to the provisions of the Air Navigation Regulations in respect of documents, records and the personal flying logbook.

SECTION 1 PERSONAL PARTICULARS OF APPLICANT (in BLOCK CAPITALS please)					
Full Name (Surname first)					
Licence Number					
Address to which licence is to be returned					
and telephone number					
SECTION 2 APPLICATION					
I apply to have the BN2 aeroplane included in the Aircraft Rating of my Pilot's Licence. I certify that the information provided on this form is true to the best of my knowledge and belief. The following is also attached in support of this application.					
Knowledge					
Evidence of a pass in the CAAF approved BN2 aeroplane type rating examination.					
Fees(Refer to Civil Aviation (Fees and Charges) Regulation)					
Type rating issue fee, and Flight test fee (if test conducted by CAAF Examiner)					
Signature Date					
SECTION 3 DECLARATION OF TRAINING AND PROFICIENCY					
This applicant has satisfactorily completed a course integrating ground and flying training on BN2 aeroplane and has demonstrated a satisfactory level of proficiency to Authorised Examiners in this aeroplane for the particular purpose in each test certified overleaf (the boxed items being completed on date) and in the following aspects of operation:					
 Use of all the equipment, fitted to this aircraft, which is the responsibility of the Flight Crew. Performance of normal, abnormal, alternate and emergency drills appropriate to the Flight Crew duties as defined in the relevant Flight and/or Company Operations Manual. Ability to carry out, at the systems panel of the aircraft, all normal in-flight procedures. 					
Pilot in charge of training for: Company					
Name (in BLOCK CAPITALS) Licence No. and Type					

Page 1 of 3

FOR OFFICIAL LISE ONLY				C	alculation
FOR OFFICIAL USE ONLY			Fee		
			Part:		
			Item:		
Examiner authority checked					
		-	Time: Frm		
ACCEPT			: To		
		-	Travel:Frm		
REJECT because:			То		
		-	Transport		
			Accommodation		
Signature Date		[Overhead		
g			Receipt No.		
			Date		
SECTION 4 CERTIFICATE OF TEST FOR AIRCRA LICENCE (AEROPLANES) I, being a person duly authorised in writing by the Civil hereby certify that I have flown in a BN2 aeroplane with	Aviation	Authority of	Fiji to conduct s	such aircraft	rating tests,
the applicant carried out satisfactorily* and unassisted, which my signature appears below, together with my nat*(See Note 2)	under the	conditions s	stated, the mano	euvres and o	
			EXAMINER		
	Date	A/c Reg.	Signa	ture	Licence
	of test		(name once	in capitals	No.

					EXAMINER		
4.1.1 Normal take-off and climb to circuit 4.1.2 Visual circuit, approach with no glide slope guidance, and full stop landing. (See Note 1) 4.1.3 Take-off with simulated failure of an engine after V1. (See Notes 3 & 5) 4.1.4 With an engine simulated failed after take off, carry out an asymmetric circuit and landing. (See Note 3 & 5) 4.1.5 Steep Turns To 45° AOB, 180° to left 180° to right 4.1.6 In clean configuration and approach to stall (to stall warning), disengage auto-pilot and recover 4.1.7 In landing configuration, stall (to nose down pitch) and recover 4.1.8 Accelerate-stop with simulated engine failure immediately before V1. (Note 3) 4.1.9 Cross Wind Take off and Landing				A/c Reg.	(name once in capitals	Licence No.	
4.1.2 Visual circuit, approach with no glide slope guidance, and full stop landing. (See Note 1) 4.1.3 Take-off with simulated failure of an engine after V ₁ . (See Notes 3 & 5) 4.1.4 With an engine simulated failed after take off, carry out an asymmetric circuit and landing. (See Note 3 & 5) 4.1.5 Steep Turns To 45° AOB, 180° to left 180° to right 4.1.6 In clean configuration and approach to stall (to stall warning), disengage auto-pilot and recover 4.1.7 In landing configuration, stall (to nose down pitch) and recover 4.1.8 Accelerate-stop with simulated engine failure immediately before V ₁ . (Note 3) 4.1.9 Cross Wind Take off and Landing	4.1	BY DAY IN AN AEROPLANE IN FLIGHT	FOR THE	SPECIFIED	ITEM.		
guidance, and full stop landing. (See Note 1) 4.1.3 Take-off with simulated failure of an engine after V ₁ . (See Notes 3 & 5) 4.1.4 With an engine simulated failed after take off, carry out an asymmetric circuit and landing. (See Note 3 & 5) 4.1.5 Steep Turns To 45° AOB, 180° to left 180° to right 4.1.6 In clean configuration and approach to stall (to stall warning), disengage auto-pilot and recover 4.1.7 In landing configuration, stall (to nose down pitch) and recover 4.1.8 Accelerate-stop with simulated engine failure immediately before V ₁ . (Note 3) 4.1.9 Cross Wind Take off and Landing	4.1.1	Normal take-off and climb to circuit					
engine after V ₁ . (See Notes 3 & 5) 4.1.4 With an engine simulated failed after take off, carry out an asymmetric circuit and landing. (See Note 3 & 5) 4.1.5 Steep Turns To 45° AOB, 180° to left 180° to right 4.1.6 In clean configuration and approach to stall (to stall warning), disengage auto-pilot and recover 4.1.7 In landing configuration, stall (to nose down pitch) and recover 4.1.8 Accelerate-stop with simulated engine failure immediately before V ₁ . (Note 3) 4.1.9 Cross Wind Take off and Landing	4.1.2	guidance, and full stop landing. (See Note					
off, carry out an asymmetric circuit and landing. (See Note 3 & 5) 4.1.5 Steep Turns To 45° AOB, 180° to left 180° to right 4.1.6 In clean configuration and approach to stall (to stall warning), disengage auto-pilot and recover 4.1.7 In landing configuration, stall (to nose down pitch) and recover 4.1.8 Accelerate-stop with simulated engine failure immediately before V ₁ . (Note 3) 4.1.9 Cross Wind Take off and Landing	4.1.3						
to right 4.1.6 In clean configuration and approach to stall (to stall warning), disengage auto-pilot and recover 4.1.7 In landing configuration, stall (to nose down pitch) and recover 4.1.8 Accelerate-stop with simulated engine failure immediately before V ₁ . (Note 3) 4.1.9 Cross Wind Take off and Landing	4.1.4	off, carry out an asymmetric circuit and					
4.1.7 In landing configuration, stall (to nose down pitch) and recover 4.1.8 Accelerate-stop with simulated engine failure immediately before V ₁ . (Note 3) 4.1.9 Cross Wind Take off and Landing	4.1.5						
4.1.8 Accelerate-stop with simulated engine failure immediately before V ₁ . (Note 3) 4.1.9 Cross Wind Take off and Landing	4.1.6	(to stall warning), disengage auto-pilot and					
failure immediately before V ₁ . (Note 3) 4.1.9 Cross Wind Take off and Landing	4.1.7						
	4.1.8						
4.1.10 Low Level Circuit	4.1.9	Cross Wind Take off and Landing					
	4.1.10	Low Level Circuit					

Page 2 of 3

4.1.11	Short Field Take Off and Landing		
4.1.12	Flapless Landing		

SECTION 5 FLYING EXPERIENCE

I have had the following flying experience on the BN2 aeroplane as recorded in my personal Pilot's Flying Logbook:

5.1	Type Conversion training:	Aeroplane Hours				
	Handling					
Signed		Date				
Certified correctTraining Manager for						
Name i	n BLOCK CAPITALS	Licence no. and type				

GENERAL NOTES

- 'A circuit' is the flight path around an aerodrome at a specified height, which facilitates an aircraft's positioning from a point on the take-off path of a given runway to a point, on the approach path of the same runway, from which a landing can be made.
- 'Satisfactorily' means that the applicant is in full control of his aeroplane at all times, and that the successful outcome
 of a manoeuvre is never in doubt. 'Unassisted' means without verbal prompting or physical assistance with the
 flying controls.
- 3. In the aeroplane 'Simulated engine failure' means with throttle lever set to idle so as to represent a failed engine as nearly as possible. The accelerate-stop tests required by this Form should be carried out as follows:
 - In the aeroplane, simulated engine failure should be initiated at a **speed and height** which will not hazard the safety of the aircraft.
 - Simulated engine failure for abort drills should be initiated at a speed which is close to V₁ but which is sufficiently below to require a decision to stop, eg V₁ -5 or -10 knots.
- 4. Endorsement of the licence will date from the completion of these tests.
- 5. Only persons holding written authorisation from the Civil Aviation Authority of Fiji in respect of the aeroplane used for this test may sign for the satisfactory completion of any test on this form.
- 6. This issue of CAAF Form PL105J is for use in respect of all BN2 aeroplanes. Copies of this form are available from the Civil Aviation Authority of Fiji, Private Mail Bag (NAP 0354), Nadi Airport, Fiji, telephone (679) 8923155 or may be downloaded from www.caaf.org.fj/index.cfm Forms & Downloads Personnel Licensing Application-Aircraft Rating –PL 105J.

Form PL 105J – Aircraft Type Rating – Aeroplane (BN2)